










MODULAR WELDING TABLE & FIXTURE


Specialised in manufacturing of modular welding table and fixture accesories

ORPEX Modular System - D16 &D28 Series









Experience the Difference


Our growth is attributed to a quality product, strong engineering background in fixture design at affordable cost for all range of product. We are committed to provide the best product in the market, reliable customer support and unmatchable service "





Why Modular fixture?

	Dedicated /Selfmade fixture	ORPEX Modular Fixture
How Many times to purchase?	Every time when you make new job	One Time
Is it easy to make changes in fixture or modify?	Difficult to make changes	Easily changes within minutes
How much time require to make fixture	Weeks/months	A matter of minutes
What if job repeats	Need to search for hours+possiblity of missing parts	Reconstruct easily
Advantages	use for specific job only	Use for all type of job,Anticorrosive,Spatter free surface zero maintenance,modular designs, Reduces distortion , zero fixture scrap,organised storage



Minimum 100 fixtures can be made with one set of tooling




Why ORPEX?


Proffesional fabricator when decided to change traditional selfmade/dedicated fixture to modular welding fixture looking forward to increase in productivity, accuracy and consistent results therefore it is important to select a high precision welding table and clamps which works best for your application.


ORPEX modular welding table & fixtures for welding has proven itself a valuable asset and wise investment for all type of fabrication unit offering best product quality in market ,innovative designs and unmatchable customer suppport. We believe in collaboration and partnerships. our engineers will interact with you to understand your project to help you selecting appropriate toollings and wedling table paltform

Quality & performance worth your trust












Machine frame fixture








Heavy Structure Frame fixture



Pipe & Flange fixture







Machine Body Welding fixtures





3D Modular Welding Table

3D modular table has features 5 working surfaces for more versatality and expandability maintaining industry-leading requirements for flatness, squareness and dimensional accuracy.

Technical Specification

Plate Material: STEEL-IS2062
Frame Material: STEEL-IS2063
Table Flatness: 0.3/1000mm
Hole Diameter: Ф16mm
Hole pitch: 50±0.038mm
Plate Thickness: 16mm

Niriding case depth: 0.01-0.02mm

Surface hardness: HV450



Model No	Length (mm)	Width(mm)	Height(mm)	Loading
				capacity
WT-3D-3015	3000	1500	750/900	2000 kg
WT-3D-2412	2400	1200	750/900	2000 kg
WT-3D-2015	2000	1500	750/900	2000kg
WT-3D-2010	2000	1000	750/900	1800 kg
WT-3D-1510	1500	1000	750/900	1000 kg
WT-3D-1212	1200	1200	750/900	1000 kg
WT-3D-1010	1000	1000	750/900	1000 kg



2D Modular Welding Table

ORPEX Modutech introduces 2D modular welding table that provides a continuous tabletop surface of precision hardened steel plates with equal spacing holes for unlimited options in setting up welding fixtures for dedicated, short run or prototype. These fixture accessories give welders proper fixturing capabilities to increase productivity and work quality.

Technical Specification

Plate Material: STEEL-IS2062 Frame Material: STEEL-IS2063 Table Flatness: 0.3/1000mm Hole Diameter: Ф16mm Hole pitch: 50±0.038mm Plate Thickness: 16mm

Niriding case depth: 0.01-0.02mm

Surface hardness: HV450



Model No	Length (mm)	Width(mm)	Height(mm)	Loading
				capacity
WT-2D-3015	3000	1500	750/900	2000 kg
WT-2D-2412	2400	1200	750/900	2000 kg
WT-2D-2015	2000	1500	750/900	2000kg
WT-2D-2010	2000	1000	750/900	1800 kg
WT-2D-1510	1500	1000	750/900	1000 kg
WT-2D-1212	1200	1200	750/900	1000 kg
WT-2D-1010	1000	1000	750/900	1000 kg



Slotted Welding Table

Slotted modular welding table is one of economical series comes with gap of 50 mm between two plate. fixturing components can be inserted into the 16 mm holes at any point on the tabletop for complete flexibility in the set-up of fixtures for dedicated, short run, one time fixtures.

Technical Specification

Plate Material: STEEL-IS2062
Frame Material: STEEL-IS2063
Table Flatness: 0.3/1000mm
Hole Diameter: Φ16mm
Hole pitch: 50±0.038mm
Plate Thickness: 16mm

Niriding case depth: 0.01-0.02mm

Surface hardness : Hv450

Gap between two plates : 50mm



Model No	Length (mm)	Width(mm)	Height(mm)	Loading capacity
WT-SL-3015	2950	1500	750/900	2500 kg
WT-SL-2412	2350	1200	750/900	2000 kg
WT-SL-2110	1950	1000	750/900	1800 kg
WT-SL-1510	1550	1000	750/900	1000 kg
WT-SL-1212	1150	1200	750/900	1000 kg
WT-SL-1010	950	1000	750/900	1000 kg



Rotary Modular Welding Table

Horizontally mount your welding tabletop on rotary positioner for rotation of platform in 360 degree around horizontal axis. The gear driven free-turning mechanism allows controlled positioning at precise 15 degree increments with positive manual locking.




Plate Material: STEEL-IS2062
Frame Material: STEEL-IS2063
Table Flatness: 0.3/1000mm
Hole Diameter: Φ16mm
Hole pitch: 50±0.038mm
Plate Thickness: 16mm

Niriding case depth: 0.01-0.02mm

Surface hardness: HV450





MAX-WL Welding Table

>> Available in 2D and Slotted option >>

ORPEX MAX size modular welding table designed for big size jobs or to perform multiple welding job at a time. Equally space holes gives infinite clamping options with accuracy and repeatability



Model No	Length	Width	Height	Loading Capacity
MAX-3D-4020	4000	2000	750/900	4000kg
MAX-3D-3020	3000	2000	750/900	3000kg
MAX-3D-2020	2000	2000	750/900	3000kg

rechnical Specification

Plate Material: STEEL-IS2062
Frame Material: STEEL-IS2063
Table Flatness: 0.3/1000mm
Hole Diameter: Ф16mm
Hole pitch: 50±0.038mm
Plate Thickness: 16mm

Niriding case depth: 0.01-0.02mm


Surface hardness : HV450





2D Modular Welding Table Size:1000x1000x750/900mm








Fixture Kit-2010

Size:2000X1000x750/900mm









Model No- LC200

Model No- LA100 Qty-6

Model No- LTR50

Model No- LS150 Qty-4

Model No- JPL68 Qty-4









Model No- VB120

Model No- LA300 Qty-4

Model No- LB28 Qty- 15

Model No- MAGSQ Qty-2

Model No- LDC200 Qty-2

SET -FS51 Application







Square Frame Fixture

Round Pipe Fixture

Sheetmetal Fixture

General Welding Fixture 11




Fixture Kit-2412

Size:2400X1200x750/900mm



Modular Welding Table(2400x1200x750/900mm) +Tool Cart+ Clamp Acccessories






Fixture Kit-3015

Size:3000X1500x750/900mm



Modular Welding Table(3000x1500x750/900mm)+ Clamp Accessories Set FS100


Fixture Set- FS100








Versatile Application of ORPEX Modular table





Locating Angles

Locating angle clamp widely used to hold job at 90°. It can also use as stopper for positioning job. The precision machined hole and slot combination allow user to make adjustments in number of clamping position anywhere on the welding table. Locating clamp can use with combination allow user to make adjustments in number of clamping position anywhere on the welding table. Locating clamp can use with combination with riser Block or any welding clamps to build any complex fixtures.





MODEL NO	Length	Width	Height	Thickness	Slot Length
LA300	150	50	300	12	100
LA150	150	30	150	12	100
LA101	150	30	100	12	100
LA100	100	30	100	12	50
LA50	100	30	50	12	50









Riser Block

Rise block are design with five clamping side of machined surface features with diagonal hole arrangements. Riser blocks use as extension for over sized job or to join tables together for over sized job. Stack riser block for vertical setup as require for fixturing. The lower base of riser block is slotted for long range of adjustment results in multiple clamping applications. Use Side plate of 3D Welding table to join multiple tables together for oversized job. Riser block is a highly versatility in combination with various orpex elements results on variety of connecting option.



Model No.	Length	Width	Height	Hole Dia
RB300	100	100	300	16
RB200	100	100	200	16
RB100	100	100	100	16









Locking Clamp


Locking clamps are designed to fits into holes of welding table platform, locating angles, locating stops, riser block etc. for fast and rigid clamping. It provides firm grip when Job are clamped while welding mainly to avoid distortion. The Locking Clamp have adjustment in vertical axis to set the height of clamp and adjustable horizontal arm for accurate clamping location by sliding the handle to any clamping position. These clamp fulfill every requirements at any clamping situation.



Model No	Width	Height	Required Diameter
LC-200	150	200	16
LC-300	200	300	16
LC-400	200	400	16








rm length can be adjusted to reach w



Locking Degree Clamp

The Degree Clamp have universal features adjustment in horizontal and vertical axis with 360 degree rotation capability along with pivoting action on arm for clamping at any angle require position. These screw clamp adapts perfectly for variable clamping range. Adjust the Ring to set the height of Degree Clamp. Place the Degree Clamp into any holes of welding table platform, locating angles, stops, riser block etc. for vertical clamping. For horizontal clamping, remove the Vertical Clamp Pipe and use Pivoting Arm directly into holes of the welding table top.






Model No	W	Н	Dia
LDC200	150	200	16

Locking Swing Clamp

The locking swing clamp into any holes of welding table platform, locating angles, stops, riser block etc. For vertical clamping horizontal clamping, remove the Vertical Clamp Pipe and use Pivoting Arm directly into holes of the welding table top.






Locating Square

Locating Squares are designed with three clamping side for use in a wide variety of clamping applications. The lower base is slotted for adjustable mounting which helps long rang of adjustment and clamping. Clamping Squares are manufactured for heavy parts can be used as table extensions, or stack clamping Squares to hold taller workpiece.




Model No	Depth	Width	Height	Slot Length
LSQ300	75	150	300	150
LSQ200	75	150	200	150
LSQ100	75	150	100	100



Locating Flat

Locating flat design to fixed at edges of welding job for creating right angle fixtures. Locating flat has hole and Long slot allows user to make adjustment in fixture. It can fix into a position to locate and stop job in 90° angle.





Model No	W	Н	Thk
LF250	200	250	12




Locking Bolt


Quick Locking Clamp is an essential element of modular fixturing components. It's fast and easiest way to lock components several times. Provide High Clamping Force with less effort. Bolts are innovative designed for locating and fastening orpex fixture elements with welding tabletop without reaching the bottom undermate of the table. Bolt have high clamping range connecting all Orpex components on the table such as welding table plate to clamp or Welding clamp to clamp. Locking Bolt are made of hardened steel which provides high strength. Locking Bolt consist of 3 steel balls in the steam. These three balls move outwards while tightening to lock components. Insert the Locking Bolt over the fixturing element and rotate the head in clockwise for initial positioning



Model	Туре	Apllication	Adj.Length	Dia
LB28	Adjustable	Connecting table and accessories /Accessories together	22-28mm	16












Locating Stop

Locating Stop have hole and slot helps for long range of adjustment and clamping flexibility. Results in multiple clamping applications. It can fix into a position to locate and stop job accurately. Long precise slot allows user to make adjustment in fixture in many ways. Stops helps to align job anywhere on the table. Stop can use be with V block for adjustable of tubular fixtures. Locating stop can combine with any welding clamps for variety of clamping option.



Model No.	Length	Width	Slot Length
LS150	150	30	100
LS200	200	30	50
LS250	250	30	125
LS300	300	50	100





Extension & Side Bracket

Side bracket can fix along the edge of 2D welding table and use as extension for large size job. It can hold right angles, flat and welding plate, gives multiple functionality to your welding table for fixturing oversized job.






Model NO	Apllication	Diameter
3DRAB	Extension	16

Toggle Clamp

Vertical Toggle clamp can fix with table top or welding clamp for hold down job. It is use for Fast and light duty clamping purpose. It can also mount on Riser Block ,Locating Square to reach required height for fixtures clamping. Slot Mounting Base for adjustment of clamp. Horizontal Toggle Clamp is use to hold job in horizontal axis. It can also mount of Riser Block, Locating Square to reach required height for fixtures clamping.










Vertical Toggle Clamp

ModelNo	Application	L	Н
VTC-200	Vertical clamping	230	200
VTC-220	Vertical clamping	240	220
HTC-100	Horizotal clamping	200	100
HTC-120	Horizotal clamping	225	120



Jaw Plier

Plier are friendly design, durable adjustable locking jaw, and comfortable to use. Locking C-Clamp Pliers opening jaws provide greater versatility in clamping a variety of jobs. Larger handle for greater clamping pressure with less effort and reduced hand fatigue. Fast and easy clamping option. Turn screw to adjust pressure and fit work. Stays adjusted for repetitive. It can clamp lock thick and large workpiece design for welding. Two swivel Pads provide a better clamping surface.



Model No	Width	Throat	Jaw
JPL-68	257	68	100
JPL-200	387	200	100








V-Block

V-Block designed to hold tubular parts, can be fit in any hole of welding table, riser block, locating angle etc. It can be use with adjustable spacers or locator to reach specific height or to alignment job for different fixture. V block can also be use with Locating stop for tubular fixturing adjustment.




Model No.	Diameter	Max Tube Size	Fitting hole
VB-90	50	50	16
VB-120	50	60	16
VB-135	60	7 5	16





Adjustable Spacer

Specifically designed for Vernier adjustments ranging from 50 – 70 mm or 75-100 mm. Precise Adjustable Spacer allows user to easily adjust vertical height of fixture. It fits into hole of table platform, locating angles, stops etc. It can be use with V blocks to reach specific height or alignment requirements





Adjustment

75-100



Diameter

40




Magnetic Clamp

Magnetic clamp use to hold metal part at 45° / 90°. MAGSQ clamps are use for fast and easy clamping of round, square tubes and flat sheet.



Model No	Pull Force	Max.tube size	Angle Lock
MAG SQ	40 kg	32	90° & 45°




Mag Pin

Magpins are use to hold light ferrous metals in place during welding and assembly. Magnetic Bolt can be inserted in the hole of locating angle, table platform or at any flat surface of welding clamps.



Model NO`	Length	Dia
MAGBOLT	42	25






Locator

Locator serves as a rest parts above the table top. It can use as a stopper for positing job. Locator can also use with V block to reach fixed height of fixture or to alignment job at fixed height







LTR12


Model No	Diameter	Height
LTR50	30	50
LTR12	30	12

Eccentric Pad

Eccentric pad design to gives scop for edge adjustment of workpiece in multiple ways.



Model No	Diameter	Thick	Offset
ECP75	75	12	20
ECP50	50	12	12





Tool Cart

Tool cart is a organized storage for clamp accessories and tools.




Model	Length	Width	Height
TC-657	630	500	700






Fixture Set-FS26



Model No- LC200 Qty-4



Model No- LS150 Qty-4



Model No- LA100 Qty-6




Model No-LB28 Qty- 10



Model No- LTR50 Qty-4

Fixture Set- FS51



Model No- LC200 Qty-6



Model No- LA100 Qty-6



Model No- LTR50 Qty-4



Model No- LS150 Qty-4



Model No- JPL68 Qty-4



Model No- VB120 Qty-4



Model No- LA300 Qty-4



Model No-LB28 Qty- 15



Model No- MAGSQ Qty-2



Model No-LDC200 Qty-2




Fixture Set-FS85












Model No- LS200 Qty-4

Model No- LS150 Qty-4

Model No- JPL68 Qty-6









Model No-LC200 Qty-8

Model No-LDC200 Qty-4

Model No-MAGSQ Qty-4

Model No-LTR50 Qty-6









Model No- LA300 Qty-4

Model No- LSQ300 Qty-2

Model No- LA100 Qty-6


Model No- LA50 Qty-4







Fixture Set - FS132



Model No- LB28

Qty- 50

Model No- LA150

Qty- 04

Model No- MAGSQ Qty- 04

Model No-TC-657

Qty-01



D28-Modular 3D Welding Table

3D modular table has features 5 working surfaces for more versatality and expandability maintaining industry-leading requirements for flatness, squareness and dimensional accuracy.



Model No	Length(mm)	Width(mm)	Height(mm)	Loading Capacity
D28-WT-3D-3015	3000	1500	750/900	3000kg
D28-WT-3D-2412	2400	1200	750/900	1800kg
D28-WT-3D-2010	2000	1000	750/900	1800kg
D28-WT-3D-1510	1500	1000	750/900	1000kg
D28-WT-3D-1212	1200	1200	750/900	1000kg
D28-WT-3D-1010	1000	1000	750/900	800kg



D28-Modular 2D Welding Table

D-28 2D modular welding table that provides a continuous tabletop surface of precision hardened steel plates with equal spacing holes for unlimited options in setting up welding fixtures for dedicated, short run or prototype.



Model No	Length(mm)	Width(mm)	Height(mm)	Loading Capacity
D28-WT-2D-3015	3000	1500	750/900	3000kg
D28-WT-2D-2412	2400	1200	750/900	1800kg
D28-WT-2D-2010	2000	1000	750/900	1800kg
D28-WT-2D-1510	1500	1000	750/900	1000kg
D28-WT-2D-1212	1200	1200	750/900	1000kg
D28-WT-2D-1010	1000	1000	750/900	800kg



Locating Angles D-28

LA28-175SL



Locating Angle LA28-175SL

Length	Width	Height	Thick
175 mm	50 mm	175 mm	25 mm



Locating Angle LA28-175HL

Length	Width	Height	Thick
175 mm	50 mm	175 mm	25 mm





Locating Angle LA28-175L

Length	Width	Height	Thick
175 mm	50 mm	175 mm	25 mm





Locating Angle LA28-275L

Length	Width	Height	Thick
275 mm	50 mm	175 mm	25 mm

LA28-200L



Locating Angle LA28-200L

Length	Width	Height	Thick
175 mm	50 mm	200 mm	25 mm



Locating Stops D-28



LS28-800/LS28-1000

10 System Clamping Holes

Length	Width	Thick
800 mm	100 mm	25 mm
1000 mm	100 mm	25 mm



LS28-500

7 System Clamping Holes

Length	Width	Thick
500 mm	75 mm	25 mm



LS28-300

3 System Clamping Holes

Length	Width	Thick	
300 mm	50 mm	25 mm	



LS28-225

1 System Clamping Holes

Length	Width	Thick	
225 mm	50 mm	25 mm	

LS28-150



LS28-150

1 System Clamping Slot

Length	Width	Thick
150 mm	50 mm	25 mm



V Block D-28

VB120/90



V Block 120 / 90

Dia	Height
58 mm	50 mm

ASP100



Adjustable Spacer 100

Dia	Height Adj
80 mm	75 - 100 mm

OCP75/100



Off Center Pad 75 / 100

Dia	Thick	
75	25 mm	
100	25 mm	

Toggle Clamps

VTC300



Vertical Toggle Clamp 300

Length	Dia
75 mm	28 mm

HTC300



Vertical Toggle Clamp 300

Length	Dia
75 mm	28 mm



Clamping And Locating Angles

CLA750



Clamping And Locating Angle750

Length	Width	Height	Thick
275 mm	85 mm	750 mm	25 mm

CLA500



Clamping And Locating Angle 500

Length	Width	Height	Thick
225 mm	75 mm	500 mm	25 mm

CLA300



Clamping And Locating Angle 300

Length	Width	Height	Thick
275 mm	75 mm	300 mm	25 mm

Locking Clamp D-28

LC300L



Locking Clamp LC300L

Width	Height
200 mm	300 mm

LC300FL



Locking Clamp LC300FL

Spindle Length	Height
180 mm	300 mm



Flat Squares D-28





Flat Square 500

5 System Clamping Holes

Length	Width	Thick	
500 mm	375 mm	25 mm	

Fs175



Flat Square 175

3 System Clamping Holes

Length	Width	Thick	
175 mm	175 mm	25 mm	

Locking Bolt D-28

LB50



Ball lock Bolts 50

Length	Dia
85 mm	28 mm

Tool Trolley

TL D28



Tool Storage Trolley D28

length	Width	Height	
1000 mm	700 mm	960 mm	



Riser Block D-28

RB28-500/1000



Riser Block 500 / 1000

Length	Width	Height	Thick
200 mm	200 mm	500 mm	25 mm
200 mm	200 mm	1000 mm	25 mm

Spacer Block D-28

SB28-300/500/1000



Spacer Block C Shape 300 / 500 / 1000

Length	Width	Height	Thick
200 mm	100 mm	300 mm	25 mm
200 mm	100 mm	500 mm	25 mm
200 mm	100 mm	1000 mm	25 mm

Universal Tilt Clamp D-28

UTC 475




Universal Tilt Angle 475

Length	Width	Height	Thick
475 mm	100 mm	100 mm	25 mm



Our Esteemed Clients





Official Website www.orpex.in

Contact us @

Email: sales@orpex.in / info@orpex.in

Contact No: 9769997861/2

Address: ORPEX MODUTECH

Gala No.B10,MI Udyog Nagar, Kharegaon,

Bhayander East Thane-401105